



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A61K 7/00, 7/48	A1	(11) International Publication Number: WO 00/61076 (43) International Publication Date: 19 October 2000 (19.10.00)
<p>(21) International Application Number: PCT/EP99/09586</p> <p>(22) International Filing Date: 2 December 1999 (02.12.99)</p> <p>(30) Priority Data: 60/129,273 14 April 1999 (14.04.99) US</p> <p>(71) Applicant (for AE AU BB CA CY GB GD GH GM IE IL KE LC LK LS MN MW NZ SD SG SL SZ TT TZ UG ZA ZW only): UNILEVER PLC [GB/GB]; Unilever House, Blackfriars, London EC4P 4BQ (GB).</p> <p>(71) Applicant (for all designated States except AE AU BB CA CY GB GD GH GM IE IL IN KE LC LK LS MN MW NZ SD SG SL SZ TT TZ UG ZA ZW): UNILEVER NV [NL/NL]; Weena 455, NL-3013 AL Rotterdam (NL).</p> <p>(71) Applicant (for IN only): HINDUSTAN LEVER LIMITED [IN/IN]; Hindustan Lever House, 165/166 Backbay Reclamation, Maharashtra, 400 020 Mumbai (IN).</p> <p>(72) Inventor: MOHAMMADI, Fatemeh; Elizabeth Arden Co., 40 Merritt Boulevard, Trumbull, CT 06611 (US).</p>	<p>(74) Agent: ROTS, Maria, Johanna, Francisca; Unilever PLC, Patent Department, Colworth House, Sharnbrook, Bedford, Bedfordshire MK44 1LQ (GB).</p> <p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report.</i></p>	
(54) Title: FOAMING COSMETIC PRODUCTS		
<p>(57) Abstract</p> <p>A foaming cosmetic product is provided which is packaged within a container fitted with pump and nozzle to express a cosmetic composition in mousse form. Foam may be generated by an agent which is a mechanical device such as a screen within a valve or by an aerosol propellant in a pressurized system. The cosmetic composition includes a crosslinked non-emulsifying polysiloxane elastomer and a carboxyvinyl polymer, the latter stabilizing the composition against separation and contributing to a rich dense foam.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

- 1 -

FOAMING COSMETIC PRODUCTS

BACKGROUND OF THE INVENTION

5 Field of the Invention

The invention concerns foamed cosmetic compositions generated by aerosol or mechanical pump action.

10 The Related Art

Foam quality of product expressed in mousse form may be greatly affected by the formulation components. For instance, many silicone compounds are anti-foam agents.

15 Collapse or at least poor quality foam often results from inclusion of silicone compounds. Yet in the area of cosmetic chemistry, silicone compounds have highly beneficial skinfeel and other properties.

20 Crosslinked non-emulsifying siloxane elastomers have been reported as being excellent cosmetic ingredients. For instance, U.S. Patent 5,833,973 (Dobkowski et al.) describes inclusion of siloxane elastomer into an aqueous emulsion to achieve improved skinfeel properties.

25 WO 97/32561 (Nawaz) describes skincare compositions including a crosslinked polyorganosiloxane polymer, silicone oil, organic liquid crystal-forming amphiphilic surfactant and water to form an oil-in-water emulsion. Gelling agents
30 such as carboxyvinyl polymers are optional further components. These compositions are reported to improve

- 2 -

skinfeel, reduce greasiness/stickiness and have faster absorption.

A poster presentation at the IFSCC International Congress in
5 Yokohama in 1992 (pages 289-296) presented by Sakuta
described the usefulness of crosslinked silicone polymers as
thickening agents for dimethylpolysiloxane. Stable water-
in-oil emulsions were reported to be obtainable by using a
polyoxyalkylene-modified silicone oil. A cosmetic
10 foundation was described wherein a Carbomer was formulated
along with the silicone elastomer and various pigments.

Although the art has recognized the usefulness of silicone
elastomers in skin cosmetics, there has been no description
15 of formulations successfully incorporating this substance
into mousse type products. Formulation of mousses presents
many challenges. These include the problems of providing
rich and stable foams, avoidance of nozzle clogage, storage
stability of concentrates and good skinfeel of the resultant
20 foamed product.

Accordingly, it is an object of the present invention to
provide a cosmetic composition in mousse form having a rich
long-lasting foam and good skinfeel.

25

Another object of the present invention is to provide a
cosmetic composition in mousse form which has good physical
stability.

- 3 -

These and other objects of the present invention will become more readily apparent from consideration of the following summary and detailed description.

5 SUMMARY OF THE INVENTION

A foaming cosmetic product is provided which includes:

- 10 (A) a container with a nozzle outlet and a foaming mechanism; and
- (B) a cosmetic composition including:
 - (i) from 0.001 to 2% by weight of a crosslinked carboxyvinyl polymer;
 - 15 (ii) from 0.1 to 30% of a crosslinked non-emulsifying siloxane elastomer; and
 - (iii) from 1 to 80% of a volatile polyorganosiloxane.

20 DETAILED DESCRIPTION OF THE INVENTION

Now it has been found that mousse products incorporating crosslinked non-emulsifying siloxane elastomers can be elegantly delivered through a pump mechanism with the
25 assistance of a crosslinked carboxyvinyl polymer. Systems for this invention are aqueous emulsions, particularly oil-in-water emulsions.

Crosslinked non-emulsifying siloxane elastomers are a first
30 essential element of this invention. They will have an average number molecular weight in excess of 2,000,

- 4 -

preferably in excess of 1,000,000 and optimally will range from 10,000 to 20 million. The term "non-emulsifying" defines a siloxane from which polyoxyalkylene units are absent. Advantageously the elastomers are formed from a

5 div vinyl compound, particularly a polymer with at least two free vinyl groups, reacting with Si-H linkages of a polysiloxane backbone such as a molecularly spherical MQ resin. Elastomer compositions are commercially available from the General Electric Company under product designation

10 General Electric Silicone 1229 with CTFA name of Cyclomethicone and Vinyl Dimethicone/Methicone Cross Polymer, delivered as 20-35% elastomer in a cyclomethicone carrier. A related elastomer composition under the CFA name of Crosslinked Stearyl Methyl Dimethyl Siloxane Copolymer is

15 available as Gransil SR-CYC (25-35% elastomer in cyclomethicone) from Grant Industries, Inc., Elmwood Park, N.J. The commercial products from General Electric and Grant Industries may be further processed by subjecting them to a high pressure (approximately 5,000 psi) treatment in a

20 Sonolator with recycling in 10 to 60 passes. Sonolation achieves a resultant fluid with elastomer average particle size ranging from 0.2 to 10 micron, preferably 0.5 to 5 micron. Viscosity is best when ranging between 300 and 20,000 cps at 25°C as measured by a Brookfield LV Viscometer

25 (size 4 bar. 60 rpm. 15 sec.).

Amounts of the elastomer may range from 0.1 to 30%, optimally from 1 to 15%, most preferably from 3 to 10% by weight of the composition.

30

- 5 -

A second element of the present invention is that of a volatile polyorganosiloxane. The term "volatile" refers to those materials having a measurable pressure at ambient conditions. Volatile polyorganosiloxanes useful herein may be cyclic or linear. Preferred cyclic silicones include polydimethylsiloxanes containing from 3 to 9 silicon atoms, preferably containing from 4 to 5 silicon atoms, generally known as cyclomethicones. Preferred linear silicone oils include the polydimethylsiloxane containing from 3 to 9 silicon atoms. The linear volatile silicones generally have viscosities of less than 5 centistokes at 25°C, while the cyclic materials have viscosities of less than 10 centistokes, the preferable range being from 0.1 to 8 centistokes. Examples of silicone oils useful in the present invention include: Dow Corning 224, Dow Corning 245, Dow Corning 344, Dow Corning 345 and Dow Corning 200 (manufactured by the Dow Corning Corporation); Silicone 7207 and Silicone 7158 (manufactured by the Union Carbide Corporation); SF1202 (manufactured by General Electric).

Amounts of the volatile polyorganosiloxane will range from 1 to 80%, preferably from 20 to 70%, optimally from 30 to about by weight of the composition.

A most important element of the present invention is that of a carboxyvinyl polymer. Most preferred are polymers known in the technology as Carbomers. These resins are essentially colloiddally water-soluble polyalkenyl polyether polymers of acrylic acid crosslinked with from 0.75 to 2% of polyallyl sucrose or polyallyl pentaerythritol. Carbomers are available from the B.F. Goodrich Company under the

trademark Carbopol. Examples include Carbopol 934, Carbopol 940, Carbopol 980, Carbopol 1382, Carbopol 1342 and Pemulen TR-1 (CTFA designation: Acrylates/10/30 Alkyl Acrylate Crosspolymer). Particularly preferred is a 2% active aqueous solution of Carbopol 1382. Amounts of the carboxyvinyl polymer on an active basis may range from 0.001 to 2%, preferably from 0.01 to 1%, more preferably from 0.3 to 0.8% by weight of the composition.

10 Cosmetic compositions of the present invention are aqueous
emulsions. Amounts of water may range from 30 to 85%,
preferably from 55 to 70% by weight. The emulsions may be
of the oil-in-water, water-in-oil or duplex variety. Most
especially, the invention is concerned with the oil-in-water
15 variety. Aqueous to oily phases will range in weight from
10:1 to 1:10, preferably from 1:1 to 2:1, optimally from
1:1 to 1.5:1.

Surfactants may be a further component of compositions according to the present invention. These may be selected from nonionic, anionic, cationic or amphoteric emulsifying agents. They may range in amount anywhere from 0.1 to 20% by weight of the composition. Illustrative nonionic surfactants are alkoxylated compounds based on C₁₀-C₂₂ fatty alcohols and acids and sorbitan. These materials are available, for instance, from the Shell Chemical Company under the Neodol trademark. Copolymers of polyoxypropylenepolyoxyethylene sold by the BASF Corporation under the Pluronic trademark are sometimes also useful. Alkyl polyglycosides available from the Henkel Corporation may also be utilized for purposes of this invention.

- 7 -

Anionic type surfactants include fatty acid soaps, sodium lauryl sulphate, sodium lauryl ether sulphate, alkyl benzene sulphonate, mono- and di-alkyl acid phosphates,
5 sarcosinates, taurates and sodium fatty acyl isethionate.

Amphoteric surfactants include such materials as dialkylamine oxide and various types of betaines (such as cocamidopropyl betaine).

10

Most advantageously the surfactant or emulsifier system is a combination of a glyceryl fatty acid ester such as glyceryl stearate in combination with an alkyl phosphate such as cetyl phosphate (available as Amphisol® A sold by the
15 Givaudan Corporation). Preferred amounts of each of these materials may range from 0.1 to 5%, optimally from 0.8 to 2.5% by weight of the composition.

Compositions of the invention may optionally contain a skin
20 conditioning agent. These agents may be selected from humectants, exfoliants or emollients.

Humectants are polyhydric alcohols intended for moisturizing, reducing scaling and stimulating removal of
25 built-up scale from the skin. Typical polyhydric alcohols include polyalkylene glycols and more preferably alkylene polyols and their derivatives. Illustrative are propylene glycol, dipropylene glycol, polypropylene glycol, polyethylene glycol, sorbitol, hydroxypropyl sorbitol,
30 hexylene glycol, 1,2-butylene glycol, 1,2,50hexanetriol, ethoxylated glycerin, propoxylated glycerin and mixtures

- 8 -

thereof. Most preferably the humectant is glycerin. Amounts of humectant may range anywhere from 1 to 50%, preferably from 10 to 40%, optimally from 25 to 25% by weight of the composition.

5

Exfoliants according to the present invention may be selected from alpha-hydroxycarboxylic acids, beta-hydroxycarboxylic acids and salts of these acids. Most preferred are glycolic, lactic and salicylic acids and their
10 ammonium, potassium or sodium salts.

When the conditioning agent is an emollient it may be selected from hydrocarbons, fatty acids, fatty alcohols and esters. Petrolatum is the most preferred hydrocarbons type
15 of emollient conditioning agent. Other hydrocarbons that may be employed include mineral oil, polyolefins such as polydecene, and paraffins such as isohexadecane (e.g. Permethyl 99® and Permethyl 101®).

Fatty acids and alcohols will have from 10 to 30 carbon
20 atoms. Illustrative of this category are pelargonic, lauric, myristic, palmitic, stearic, isostearic, hydroxystearic, oleic, linoleic, ricinoleic, arachidic, behenic and erucic acids and alcohols. Ester emollients based on the fatty acids, polyalkoxylated derivatives of the
25 fatty acids or alcohols and combinations thereof may also be useful. Vegetable derived ester can be similarly effective. Examples include soybean oil, cottonseed oil and maleated soybean oil.

- 9 -

Amounts of the skin conditioning agent may range from 1 to 50%, preferably from 3 to 25%, optimally from 5 to 20% by weight of the composition.

5 Preservatives can desirably be incorporated into the compositions of this invention to protect against the growth of potentially harmful microorganisms. While it is in the aqueous phase that microorganisms tend to grow, microorganisms can also reside in the oil phase. As such,
10 preservatives which have solubility in both water and oil are preferably employed in the present compositions. Suitable traditional preservatives are alkyl esters of parahydroxybenzoic acid. Other preservatives which have more recently come into use include hydantoin derivatives,
15 propionate salts, and a variety of quaternary ammonium compounds. Cosmetic chemists are familiar with appropriate preservatives and routinely choose them to satisfy the preservative challenge test and to provide product stability. Particularly preferred preservatives are methyl
20 paraben, propyl paraben, imidazolidinyl urea, sodium dehydroacetate and benzyl alcohol. The preservatives should be selected having regard for the use of the composition and possible incompatibilities between the preservatives and other ingredients in the emulsion. Preservatives are
25 preferably employed in amounts ranging from 0.01% to 2% by weight of the composition.

A further essential element of foaming cosmetic products according to the present invention is a foaming mechanism.
30 This mechanism may be in the form of a mechanical device or it can be an aerosol propellant. When it is a mechanical

- 10 -

device it will be employed with a non-aerosol dispenser. Illustrative is a dispenser characterized by a container for storing the cosmetic composition, a dispensing head defined by a housing containing a pump, and a diptube for
5 transferring the composition from the container into the dispensing head. Foam is created by requiring the composition to pass through a screen material which may be a porous substance such as a sintered material, a wire (plastic or metal) gauze screen or similar structures.

10 Suitable dispensers are described in U.S. Patent 3,709,437 (Wright), U.S. Patent 3,937,364 (Wright), U.S. Patent 4,022,351 (Wright), U.S. Patent 4,147,306 (Bennett), U.S. Patent 4,184,615 (Wright), U.S. Patent 4,598,862 (Rice),
15 U.S. Patent 4,615,467 (Grogan et al.) and U.S. Patent 5,364,031 (Tamiguchi et al.). Most preferred however is a device sold by the Airspray International Corporation described in WO 97/13585 (Van der Heijde). All these patents are incorporated herein by reference. The Airspray
20 device comprises a container for storing a cleansing composition and dispensing head, the latter including at least a concentric air pump and liquid pump. Each of the pumps has a piston chamber with a piston displaceable therein and an inlet and discharge, and an operating
25 component for operating the two pumps. The operating component is integral with one of the pistons and comprises an outflow channel with a dispensing opening. Shut-off mechanisms, rendering it possible to suck up air or liquid, respectively, and dispense them, are present in the inlet
30 and discharge of the pumps. The air pump includes a double-acting shut-off device which can be operated actively by the

- 11 -

operating component. The shut-off device prevents both the inlet of air to the pump and discharge of air therefrom. The air piston is able to be moved freely at least over a small distance with respect to the operating component.

5

Aerosol propellants in pressurized metal cans or in suitable bottles may also be employed as a foam mechanism.

Propellants which may be used include C₁-C₆ alkyl ethers, C₃-C₆ hydrocarbons, halocarbons, carbon dioxide and mixtures

10 thereof. Illustrative hydrocarbons include n-butane, isobutane, isobutane/propane mixtures all of which are available from the Phillips Petroleum Company under the respective trademarks A17, A31, A46 and A70. Among the alkyl ethers, more prominent is dimethyl ether, diethyl
15 ether, methyl ether ether and diisopropyl ether. Most preferred is dimethyl ether. Halocarbons can include dichlorodifluoromethane, dichlorotetrafluoroethane, chlorotrifluoromethane and mixtures thereof. Amounts of propellant may range from 1 to 40%, preferably from 2 to
20 15%, optimally between 3 and 12% by weight based on the cosmetic composition and propellant combination. Nozzles for the aerosols may be regulated by valves such as those available from the Precision Valve Company.

25 The following examples will more fully illustrate the embodiments of this invention. All parts, percentages and proportions referred to herein and in the appended claims are by weight unless otherwise illustrated.

- 12 -

EXAMPLES 1-8

The following formulations illustrate cosmetic compositions which are incorporated into a non-aerosol pump with a nozzle
5 communicating with an Airspray Company screen foaming device.

- 13 -

TABLE I

COMPONENT	EXAMPLE (WEIGHT %)									
	1	2	3	4	5	6	7	8	9	10
PHASE A										
Carbopol 1382® (2% Active)	5.0	5.0	10.0	10.0	1.0	1.0	1.0	5.0	5.0	15.0
Disodium EDTA	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
Butylene Glycol	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7
Glycerin	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9
Allantoin	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Colorant	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.12
Water	Bal.	Bal.	Bal.	Bal.	Bal.	Bal.	Bal.	Bal.	Bal.	Bal.
PHASE B										
Primrose Oil	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Elefac-205®	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Borage Oil	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Tridecyl- salicylate	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Alpha-Bisabolol	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
Glyceryl Stearate	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Cetyl Alcohol	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
Vitamin E Acetate	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Preservatives	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
Amphisol A®	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
PHASE C										
Water	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8
Triethanolamine	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Panthenol	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
PHASE D										
Cyclomethicone	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Silicone Elastomer *7.5% Elastomer Solids in Cyclomethicone)	25.0	30.0	15.0	5.0	30.0	10.0	25.0	10.0	5.0	25.0
Fragrance	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2

- 14 -

EXAMPLE 11

A study was conducted to evaluate Carbopol® as a storage stability enhancer. The cosmetic composition (concentrate) of Example 1 (herein designated as Sample 1) served as a representative of the present invention. Test Samples 2 and 3 were respectively the formulation of Example 1 but without Carbopol 1382® and without silicone elastomer. These three formulations were stored for two days at 60°C.

10

TABLE II

PERFORMANCE RESULTS	SAMPLE		
	1	2	3
Stability	No separation	Separation	Separation
Skin Feel	Silky feel	Not silky	Not silky
Foam	Easy to foam from pump	Pump needs to be primed several times before foam generates	Pump needs to be primed several times before foam generates

Based on the above results, it is evident that the presence of both the Carbomer and the silicone elastomer are required to achieve a stable product, having a nice silky skinfeel and readily foamable from a mechanical pump.

The foregoing description and examples illustrate selected embodiments of the present invention.

- 15 -

CLAIMS

1. A foaming cosmetic product which comprises:
 - 5 (A) a container with a nozzle outlet and a foaming mechanism; and
 - (B) a cosmetic composition comprising:
 - 10 (i) from 0.001 to 2% by weight of the composition of a crosslinked carboxyvinyl polymer;
 - (ii) from 0.1 to 30% by weight of the composition of a crosslinked non-emulsifying siloxane elastomer; and
 - 15 (iii) from 1 to 80% by weight of the composition of a volatile polyorganosiloxane.
2. The product according to claim 1 wherein the foaming mechanism is a mechanical device with at least one mesh
20 screen for generating foam.
3. The product according to claim 1 or 2 wherein the foaming mechanism is a propellant.
- 25 4. The product according to claim 3 wherein the propellant is selected from C₁-C₃ alkyl ether, C₃-C₆ hydrocarbon, halocarbon, carbon dioxide and mixtures thereof.

International Application No
PCT/EP 99/09586

According to International Patent Classification (IPC) or to both national classification and IPC

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A61K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, X	CHEMICAL ABSTRACTS, vol. 131, no. 8, 23 August 1999 (1999-08-23) Columbus, Ohio, US; abstract no. 106625, KONNO, YOSHIKAZU: "Cleansing cosmetics containing partially crosslinked polyorganosiloxanes and anionic surfactants" XP002132998 abstract & JP 11 193214 A (KOSEI CO., LTD., JAPAN) 21 July 1999 (1999-07-21)	1
Y	EP 0 240 349 A (PROCTER AND GAMBLE CO., USA) 7 October 1987 (1987-10-07) page 2, line 53 -page 3, line 57 examples 2,4-8 claims 1-13	1-4

-/-

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "A" document member of the same patent family

Date of the actual completion of the international search

14 March 2000

Date of mailing of the international search report

24/03/2000

Name and mailing address of the ISA
European Patent Office, P.B. 6818 Patentlaan 2
NL - 2280 MV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3018

Authorized officer

Bazzanini, R

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 99/09586

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 97 32561 A (PROCTER & GAMBLE ; NAWAZ ZAHID (GB); OWEN EDWARD (GB)) 12 September 1997 (1997-09-12) page 9, line 1-12 examples 1-5	1-4
A	WO 98 00103 A (UNILEVER PLC ; UNILEVER NV (NL)) 8 January 1998 (1998-01-08) tables 1-3 claims 1-3	1-4
A	WO 97 44010 A (COLGATE PALMOLIVE CO) 27 November 1997 (1997-11-27) page 9, line 24 - line 28	1-4
A	US 4 022 351 A (WRIGHT HERSHEY EARL) 10 May 1977 (1977-05-10) cited in the application abstract column 1, line 10-14	1-4

INTERNATIONAL SEARCH REPORT

information on patent family members

PCT/E

Patent document cited in search report	Publication date	Patent family member(s)	
JP 11193214 A	21-07-1999	NONE	
EP 0240349 A	07-10-1987	US 4764363 A	5-08-1988
		AU 612557 B	12-07-1991
		AU 7103987	06-10-1997
		CA 1297793	24-07-1997
		GB 2188644 A	07-1988
		JP 6302201 A	1988
		MX 161	1988
WO 9732561 A	12-09-1997	AU 205120 A	19-1997
		CA 2241326 A	12-09-1997
		CN 121531	28-04-1999
		CZ 98027	13-01-1999
		EP 0906511 A	07-04-1999
		JP 11506126 T	02-06-1999
WO 9800103 A	08-01-1998	AU 2961197 A	21-01-1998
		ZA 9701943 A	07-09-1998
WO 9744010 A	27-11-1997	US 5919437 A	06-07-1999
		AU 3073597 A	09-12-1997
		BR 9709032 A	03-08-1999
		CA 2252914 A	27-11-1997
		CZ 9803831 A	17-03-1999
		EP 0909162 A	21-04-1999
		PL 329942 A	26-04-1999
		ZA 9704478 A	23-11-1998
US 4022351 A	10-05-1977	AR 206747 A	13-08-1976
		AT 353674 B	26-11-1979
		AT 186076 A	15-04-1979
		AU 501166 B	14-06-1979
		AU 1199676 A	22-09-1977
		BE 839564 A	01-07-1976
		BR 7601991 A	05-10-1976
		CA 1058580 A	17-07-1979
		CH 617632 A	13-06-1980
		DD 124871 A	16-03-1977
		DE 2610129 A	14-10-1976
		DK 125376 A,B,	04-10-1976
		FI 760669 A,B,	04-10-1976
		FR 2306141 A	29-10-1976
		FR 2340259 A	02-09-1977
		GB 1478607 A	06-07-1977
		GR 59893 A	15-03-1978
		IE 43082 B	17-12-1980
		IL 49228 A	30-09-1979
		IN 144933 A	29-07-1978
		IT 1058049 B	10-04-1982
		JP 1327126 C	16-07-1986
		JP 51125581 A	02-11-1976
		JP 59000271 B	06-01-1984
		NL 7602828 A,B,	05-10-1976
		NO 760890 A,B,	05-10-1976
		PT 64965 A,B	01-05-1976
		RO 68804 A	10-05-1982
		SE 410268 B	08-10-1979

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/EP 99/09586

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4022351 A		SE 7603177 A	04-10-1976
		SU 632293 A	05-11-1978
		US 4018364 A	19-04-1977
		US 4184615 A	22-01-1980
		ZA 7601552 A	30-03-1977